COREPEL FLOORS · CLEANING AND CARE

Keep your COREPEL floor looking great

For COREPEL SPC (click) and PRO LINE Dryback · Checklist for your home

CLEANER	FIRST MOPPING	MOPPING
pH-neutral (pH 6–9)	**click 24 h* · Dryback 72 h**	**damp, never wet**
CHAIR CASTORS	**FURNITURE**	**NEVER**
soft, type W (EN 12529)	**felt pads, no rubber feet**	**wax, oil, steam, abrasives**

COREPEL floors have a factory-applied UV coating with a super-matt surface. They need no sealing, wax or oil. Dry cleaning, occasional damp mopping and a few precautions keep the floor looking good for many years.

01 FIRST CLEANING AFTER INSTALLATION

- Dry cleaning straight away. Damp-mop SPC click after 24 hours*, bonded Dryback after 72 hours.
- Remove dust and installation debris with a soft broom or vacuum (hard-floor head, no rotating brush).
- Mop with a well wrung-out microfibre mop and pH-neutral cleaner. Repeat after building work until the water stays clear.
- Damp-mop with clean water and let the floor dry.

02 DAILY CARE

- Sweep or vacuum loose dirt and sand. Sand acts like sandpaper.
- Wipe up spills at once, especially liquids near joints.

03 REGULAR CARE (WEEKLY OR AS NEEDED)

- Damp-mop with pH-neutral cleaner at the dose stated by its maker. Too much cleaner leaves a film.
- No standing water: wring out the mop well. The floor should be dry within minutes.
- If you see streaks, mop once more with clean water.

04 REMOVING STAINS

Always test on an inconspicuous spot first, then mop with clean water.

Coffee, tea, juice, red wine	wipe up at once, pH-neutral cleaner
Grease, oil, shoe polish	isopropyl alcohol on a soft cloth
Pen, marker, lipstick	isopropyl alcohol on a soft cloth
Heel and rubber marks	dry microfibre cloth, else isopropyl alcohol
Chewing gum, candle wax	harden with ice, lift with a plastic scraper
Hair dye, iodine, coloured disinfectant	remove at once, may stain permanently

05 PREVENT AND PROTECT

- Doormat at every entrance, without rubber or latex backing.
- Felt pads under all furniture; check and replace them regularly. Dirty pads scratch.
- Office chairs with soft castors (type W, EN 12529) or on a suitable floor protection mat.
- No contact with rubber (furniture feet, mat backings, tyres): plasticisers can cause permanent brown stains.
- Lift heavy furniture, do not drag it. Cover the floor when moving house.
- Shade strong, constant sunlight (blinds, curtains).
- Put plant pots on waterproof saucers with a felt pad, never ceramic saucers directly on the floor. No standing water.

06 NEVER USE

- Wax, oil, polish, soap cleaners that leave a residue
- Abrasives, steel wool, hard brushes, scrubbers with metal parts
- Solvents such as acetone, thinners, turpentine; vinegar, bleach, ammonia
- Steam cleaners and wet vacuums
- Standing water or flooding (excluded from the guarantee)

A damaged COREPEL SPC plank can be replaced without lifting the whole floor – ask your COREPEL partner. Damage caused by improper cleaning or care is excluded from the manufacturer's guarantee.

* Only if acrylic or silicone joints were used at skirting boards or transitions. Without joint sealant you can damp-mop straight away.

SWISS KRONO TEX GmbH & Co. KG · Wittstocker Chaussee 1 · 16909 Heiligengrabe · Germany · service@corepel-floors.com

Status 11/2026