COREPEL FLOORS · DATA SHEET

PRO LINE Dryback

LVT vinyl flooring for full-surface bonding · 4 oak designs

Designs: Brown Oak (S41392) · Beige Oak (S41402) · Nature Oak (S41412) · Warm Oak (S41422). Embossed in register, super-matt. Waterproof, glue-down installation for residential and commercial projects.

FEATURES	VALUE	STANDARD
Use class	33	EN 16511
Thickness	2.5 mm	EN 17539
Width	238 mm	EN 17539
Length	1520 mm	EN 17539
Planks per box	10	
Box content	3.62 m²	
Box weight	16.36 kg	
Bevel	Microbevel, 4-sided	
Wear layer	0.55 mm	ISO 24340:2006 (E)
Surface	EiR / Synchropore, UV coating	
Dimension tolerance	L ± 0.4 mm · W ± 0.1 mm	EN 17539
Overall thickness tolerance	± 0.15 mm	EN 17539
Wear layer tolerance	± 0.02 mm	ISO 24340:2006 (E)
Straightness / squareness	≤ 0.15 mm	EN 17539
Dimensional stability	≤ 0.15 %	EN ISO 23999
Curling after exposure to heat	≤ 1.5 mm	EN ISO 23999
Reaction to fire	Bfl-s1	EN 13501-1
Residual indentation	≤ 0.1 mm	ISO 24343-1
Slip resistance	DS	EN 13893
Microscratch resistance	B2	EN 16094
Underfloor heating	suitable (max. 27 °C surface)	
Formaldehyde-free	yes	
VOC emissions	tested (TÜV PROFiCERT Interior PREMIUM)	
Phthalate-free	yes	

Note: This information has been carefully compiled, but we cannot guarantee its accuracy, completeness or timeliness. Due to ongoing product development and possible changes in standards and laws, our technical data sheets do not constitute a legally binding assurance. It is the responsibility of the user to check the suitability and processing of the products for the respective application and to observe the legal and technical requirements. Our general terms and conditions remain unaffected.